



Representative Image

## Alternate Catalog No. ESB20-20N-01 Catalog No. 1SBE121111R0120

**Description:** ESB20-20N-01 Installation Contactor

**UPC No** 3471523007352

**Home > Contactors & Starters > UL Listed IEC Contactors > AF Contactors**

The ESB20..N installation contactors are used to control single loads up to 20 A and can be operated by AC or DC voltages. These contactors are made for use in household applications as well as in industrial environments. The following benefits are provided: Hum-free operation, low power consumption and integrated overvoltage protection. Various contact combinations and accessories are available.

### Descriptors

|          |               |
|----------|---------------|
| Category | AF Contactors |
|----------|---------------|

### Specifications

|  |  |
|--|--|
| Product Type                                       | Installation Contactors (2-poles)  |
| General Use Rating UL/CSA                          | (acc. to UL 240 V) 20 A  |
| Object Classification Code                         | Q  |
| Rated Control Circuit Voltage                      | 24 V   |
| Number of Main Contacts NO                         | 2  |
| Number of Main Contacts NC                         | 0  |
| Maximum Operating Voltage UL/CSA                   | Main Circuit 240 V AC  |
| Connecting Capacity Main Circuit UL/CSA            | Solid 14-8 american wire gauge<br>Stranded 14-8 american wire gauge  |
| Connecting Capacity Main Circuit UL/CSA            | Solid 14-8 american wire gauge<br>Stranded 14-8 american wire gauge  |
| RoHS Status  | Following EU Directive 2011/65/EU  |
| Reference Ambient Air Temperature                  | Operation -25 ... +55 °C   |
| Rated Operational Voltage                          | Main Circuit 220 V DC<br>Main Circuit 250 V AC   |
| Resistance to Shock acc. to IEC 60068-2-27         | 11 ms Pulse 15g  |
| Tightening Torque UL/CSA                           | Control Circuit 8 in-lb (pound inch)<br>Main Circuit 11 in-lb (pound inch)   |
| Rated Operational Current AC-1                     | (NO) 20 A  |
| Standards  | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>UL 60947-1<br>UL 60947-4-1<br>IEC/EN 61095   |
| Rated Operational Power AC-3                       | (230 V) Single Phase, NO 1.3 kW  |
| Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1 | 8 x I <sub>e</sub> / AC-3  |
| Horsepower Rating UL/CSA                           | (220 ... 240 V AC) Single Phase, NO 1 hp   |
| Rated Frequency                                    | Control Circuit DC<br>Control Circuit 50 Hz<br>Control Circuit 60 Hz<br>Control Circuit 400 Hz<br>Main Circuit DC<br>Main Circuit 50Hz<br>Main Circuit 60 Hz |
| Rated Short-time Withstand Current                 | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 72 A  |

## Specifications

|  |  |
|--|--|
| Rated Operational Current AC-3                   | (230 V) Single Phase, NO 9 A   |
| Rated Making Capacity AC-3 acc. to IEC 60947-4-1 | 10 x I <sub>e</sub> / AC-3   |
| Maximum Electrical Switching Frequency           | AC-1 cycles per hour<br>AC-3 cycles per hour<br>AC-7a cycles per hour<br>AC-7b cycles per hour   |
| Short-Circuit Protective Devices                 | gG Type Fuses 20 A   |
| Rated Insulation Voltage                         | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 400 V   |
| Mechanical Durability                            | 1000000 cycle  |
| Coil Operating Limits                            | (acc. to IEC 60947-4-1) 0.85 ... 1.1 x U <sub>c</sub> (at $\theta \leq 55$ °C)   |
| Secondary Rated Impulse Withstand Voltage        | 6 kV   |
| Connecting Capacity Main Circuit                 | Flexible with Ferrule 1x 1 ... 6/2x 1 ... 2.5 square mm/square mm<br>Flexible with Insulated Ferrule 1x 1 ... 6/2x 1 ... 1.5 square mm/square mm<br>Flexible 1x 1 ... 6/2x 1 ... 4 square mm/square mm<br>Rigid 1x 1 ... 10/2x 1 ... 4 square mm/square mm                   |
| Connecting Capacity Control Circuit              | Flexible with Ferrule 1x 1 ... 2.5/2x 0.75 ... 1.5 square mm/square mm<br>Flexible with Insulated Ferrule 1x 1 ... 2.5/2x 0.75 ... 1 square mm/square mm<br>Flexible 1x 1 ... 2.5/2x 1 ... 1.5 square mm/square mm<br>Rigid 1x 0.5 ... 4/2x 0.75 ... 2.5 square mm/square mm |
| Coil Consumption                                 | Average Holding Value 50 / 60 Hz 2.5 V - A<br>Average Pull-in Value 50 Hz 2.5 V - A<br>Average Pull-in Value 60 Hz 2.5 V - A<br>Average Holding Value DC 2.5 W<br>Average Pull-in Value DC 2.5 W   |
| Mounting on DIN Rail                             | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715   |
| Wire Stripping Length                            | Control Circuit 7 mm<br>Main Circuit 10 mm   |

## Classifications

|          |  |
|----------|--|
| ETIM 6.0 | EC001653 - Installation contactor for distribution board |
| ETIM 7   | EC001653 - Installation contactor for distribution board |
| ETIM 5.0 | EC001653 - Installation contactor for distribution board |
| eClass   | 7.0 27142308   |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Weight         | 0.14kg |
| Product Net Depth / Length | 65 mm  |
| Product Net Width          | 18 mm  |
| Product Net Height         | 85 mm  |

## Package Information

|                                |         |
|--------------------------------|---------|
| Package Level 1 Width          | 20 mm   |
| Package Level 1 Height         | 89 mm   |
| Package Level 1 Depth / Length | 73 mm   |
| Package Level 1 Units          | 1 piece |
| Package Level 1 Gross Weight   | 0.14 kg |

## Ordering

|                        |   |
|------------------------|---|
| Minimum Order Quantity | 1 |
|------------------------|---|

**Ordering**

Customs Tariff Number

85365080